

Overzicht deursets volgens brandwerendheid EI₁

				<31dB	37 dB / 38 dB	41dB / 42 dB
EI, 30' brandwerend	niet inbraakwerend	WoodPlus / WoodFlex	Draaideur	(40 mm) P1, P2, P3 (50 mm) P5	(50 mm) R1, R3	(54 mm) R5
		WoodBlock Rubberwood		(40 mm) P1, P2, P3 (50 mm) P5	(50 mm) R1, R3	(54 mm) R5
		WoodBlock Hardhout		(40 mm) P1, P2, P3 (50 mm) P5	(50 mm) R1, R3	(54 mm) R5
		DuoFlex		(40 mm) PA (50 mm) PB	(50 mm) R2, R3	(54 mm) R5
	WoodPlus	Zwaardeur	(50 mm) EE			
	Houten raamwerk	Schurtduur	(40 mm) EF			
	WK2 inbraakwerend	Wood Secure Rubberwood	Draaideur	(40 mm) SK	(50 mm) SL	(54 mm) SM
		Wood Secure Hardhout		(40 mm) SK	(50 mm) SL	(54 mm) SM
		DuoFlex		(40 mm) S1	(50 mm) S3	(54 mm) S4, S5
				(54 mm) S6		
DuoFlex				(54 mm) S6	(54 mm) S4	
Steel Secure			(70 mm) deur met metalen kader			
EI, 60' brandwerend	niet inbraakwerend	WoodPlus / WoodFlex	Draaideur	(50 mm) Q1		
		WoodBlock Rubberwood		(50 mm) Q1		
		WoodBlock Hardhout		(50 mm) Q1		

